

## TEMPOFLUX time flow urinal valve

Ref. 778755

Time flow 3 seconds. For standard urinals Ø 35mm. Straight neck tube






### DESCRIPTION

TEMPOFLUX time flow urinal valve - Ref. 778755





Exposed time flow urinal valve:  
 For standard or siphon action urinals.  
 For wall-mounted exposed installation.  
 Soft-touch operation.  
 Time flow pre-set at 3 seconds.  
 Vacuum breaker.  
 Flow rate pre-set at 0.15 l/sec. at 3 bar, can be adjusted up to 0.3 l/sec.  
 Innovative stopcock and flow rate adjustment system integrated in the wall plate (patented).  
 Complies with European standard EN 12541 (acoustic level class II).  
 Chrome-plated solid brass body M $\frac{1}{2}$ ".  
 With a chrome-plated neck tube and connection washer Ø 35mm.  
 Angled for recessed inlet .  
 Suitable for people with reduced mobility.  
 10-year warranty.

### TECHNICAL CHARACTERISTICS

TEMPOFLUX time flow urinal valve - Ref. 778755

|            |   |
|------------|---|
| Connector  | $\frac{1}{2}$ "   |
| Technology | Time flow   |
| Height     | 320mm   |
| Flow rate  | 0.15 l/sec.   |
| Norms      |   |
| Warranty   |    |

### ADVANTAGES

-  Eco time flow 3 seconds
-  Soft-touch operation
-  Stopcock built-in to wall plate
-  Smooth design

