

DESIGNPREIS
2006
NOMINEE



reddot design award
winner 2005

KWC-No.	Finish
10.111.102.000FL	all chrome
A 190, flexible connection hoses	
10.111.102.700FL	stainless steel
A 190, flexible connection hoses	



product
design
award

2006

Kitchen

EDELSTAHL
STAINLESS STEEL

Lever mixer


- Lever installation possible on the right or left side
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out aerator covered
 - Neoperl® Caché®
 - up to 600 mm pull-out length
 - hose surface to fit faucet surface
- Hose guide, swivelling 320°
- EasyLock - a pull-out spray that easily slides back into place
- KWC cartridge M 35
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm

Flow rate 11 l/min (3 bar)
Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.

KWC EVE

KWC

DESIGNPREIS
2006
NOMINEEreddot design award
winner 2005

KWC-No.	Finish
10.121.103.000FL	all chrome
A 225, flexible connection hoses, mains receiver	
10.121.103.700FL	stainless steel
A 225, flexible connection hoses, mains receiver	

product
design
award

2006

Kitchen
with LEDShineLUMINAQUA®
Advanced Light TechnologyEDELSTAHL
STAINLESS STEEL


Lever mixer

- Lever installation possible on the right or left side
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out aerator covered
 - Neoperl® Caché®
 - integrated ON/OFF push-button with automatic shut-off after 45 minutes
 - up to 600 mm pull-out length
 - hose surface to fit faucet surface
- Hose guide, swivelling 320°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6.75 V / cable length 1100 mm

Flow rate 10 l/min (3 bar)
Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.

www.kwc.com 22.04.2021



DESIGNPREIS
2006
NOMINEE



reddot design award
winner 2005

KWC-No.	Finish
10.121.103.150FL	glacier white

A 225, flexible connection hoses, mains receiver



product
design
award

2006

Kitchen with LEDShine

LUMINAQUA®
Advanced Light Technology


Lever mixer

- Lever installation possible on the right or left side
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out aerator covered
 - Neoperl® Caché®
 - integrated ON/OFF push-button with automatic shut-off after 45 minutes
 - up to 600 mm pull-out length
- Hose guide, swivelling 320°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6.75 V / cable length 1100 mm

Flow rate 10 l/min (3 bar)
Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.

KWC EVE

DESIGNPREIS
2006
NOMINEEreddot design award
winner 2005

KWC-No.	Finish
10.121.103.151FL	black chrome-plated
A 225, flexible connection hoses, mains receiver	

product
design
award

2006

Kitchen
with LEDShineLUMINAQUA®
Advanced Light Technology

Lever mixer

- Lever installation possible on the right or left side
- TouchProtect - anti-scald protection thanks to the "double skin" principle
- Pull-out aerator covered
 - Neoperl® Caché®
 - integrated ON/OFF push-button with automatic shut-off after 45 minutes
 - up to 600 mm pull-out length
- Hose guide, swivelling 320°
- EasyLock - a pull-out spray that easily slides back into place
- OptimalSpace - ample space for washing or working
- KWC cartridge M 35
 - with ceramic discs
 - flow rate and temperature continuously variable
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm
- Scope of delivery:
 - Mains receiver 100-240 V / operating voltage 6.75 V / cable length 1100 mm

Flow rate 10 l/min (3 bar)
Acoustic group I

Subject to technical, range and model changes. Dimensions in mm.