


Submersible pump GTF 1000 / KTP 1000 without float switch, 10 m, 230 V



Article information

Item no.: 28760
GTIN: 4026092044520
Discount group: 05

Description

Submersible pump for faecal-free wastewater, type KTP 1000, new designation: GTF 1000
Type of wastewater: wastewater without sewage

General characteristics:

Standard: EN 12050-2
Pressure pipe connection: R 1 1/4"

Pumping device:

Pump: GTF 1000
Max. pumping capacity: 14 m³/h
Max. pumping height: 10 m
Operating voltage: 230 V
Mains frequency: 50 Hz
Operating mode: S3 - 50 %
Power P1: 1.3 kW
Power P2: 0.75 kW
Speed: 2,700 U/min
Type of fuse required (electrical protection): C 16 A

Max. temperature (permanent) of conveyed material:	35 °C
Connection type:	coded plug
Length of mains cable for pump:	10 m
Rated current:	5.6 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm ²
Temperature monitoring:	integrated
Cos phi - power factor:	0.97
Expected service life (number of switching cycles):	150,000
Expected service life (hours of operation):	5,000 Std
Insulation class:	F
Max. permissible switching frequency:	20 1/h