

Practicus basement drain DN 100, vert., Black slotted grating



Article information

Item no.: 45210.40
GTIN: 4026092033005
Discount group: 01

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Version:

Odour trap: included

General characteristics:

Nominal size (DN): 100
Outer diameter (OD): 110
Standard: EN 1253-2

Dimensions:

Length: 135 mm
Width: 135 mm
Cutout dimension, length: 180 mm
Cutout dimension, width: 180 mm

Tank:

Number of outlets: 1 ST
Installation depth: 221 - 277 mm

Drain body:

Material of drain body: PP

Socket version:	vertical
Vertical adjustment:	vertically adjustable upper section
Vertical adjustment:	20 - 76 mm

Coverage features:

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Height:	16 mm
Sludge bucket:	no
Locking:	screwed

Grating:

Rim length:	150 mm
Rim width:	150 mm
Rim material:	Polymer
Upper section material:	Polymer
Discharge rate (l/s) with 10 mm backwater:	1,0 l/s
Discharge rate (l/s) with 20 mm backwater:	2 l/s