


Uponor S-Press elbow adap. female thread 40-Rp1 1/2"FT

1046910

- Made of tin-plated brass
- Fast installation with easy bevel and without calibration
- Colour code



Application information Uponor S-Press elbow adap. female thread

Specification

- with fixed press sleeve
- stop ring
- test safety

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

- if not different mentioned:


Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
- AENOR

Uponor S-Press elbow adap. female thread 40-Rp1 1/2"FT

1046910



Technical data

Item no VVS 045472042

Item (unit of measurement) Piece

Female thread Rp 1 1/2 inch

Length (l1) 59 mm

Length (l2) 75 mm

Z-measurement z2 37 mm

Packaging Quantity PL1 5

Packaging Quantity PL4 500

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com