


Uponor S-Press PLUS tee reducer 25-20-16

1070575

- Made of tin-plated DR brass



Application information Uponor S-Press PLUS tee reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS tee reducer 25-20-16

1070575



Technical data

Item no VVS	045476335
Item no NRF	5114501
Item (unit of measurement)	Piece
Length (I1)	44 mm
Length (I2)	40 mm
Length (I3)	36 mm
Z-measurement z2	19 mm
Z-measurement z3	17 mm
Packaging Quantity PL1	5
Packaging Quantity PL3	40
Packaging Quantity PL4	1920

Documents

Page with all documents



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com