

Qty. Description

1 **SQE 3-65**



Note! Product picture may differ from actual product

Product No.: [96510159](#)

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid: Water
 Liquid temperature range: 0 .. 35 °C
 Selected liquid temperature: 20 °C
 Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 10700 rpm
 Rated flow: 3 m³/h
 Rated head: 70 m
 Approvals: CE,PCBC,RCM,EAC,CN RoHS Exempt,Morocco
 Curve tolerance: ISO9906:2012 3B

Materials:

Pump: Stainless steel
 EN 1.4301
 AISI 304
 Impeller: Composite
 ZYTEL 70G30 HSLR PA6.6-GF30
 Motor: Stainless steel
 DIN W.-Nr. 1.4301
 AISI 304

Installation:

Maximum operating pressure: 15 bar
 Pump outlet: Rp1 1/4
 Minimum borehole diameter: 76 mm

Electrical data:

Motor type: MSE3
 Power input - P1: 1.55 kW
 Rated power - P2: 1.15 kW
 Power input P3: 1.1 kW
 Mains frequency: 50 Hz
 Rated voltage: 1 x 200-240 V



Company name: Tengih ehf

Created by:

Phone:

Date: 11/02/2022

Qty.	Description
	<p>Rated current: 8.4 A Power factor: 1.00 Rated speed: 10700 rpm Start. method: direct-on-line Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 1.5 m Motor No: 96160855</p> <p>Others: Net weight: 5.04 kg Gross weight: 5.76 kg Shipping volume: 0.01 m³ Danish VVS No.: 388443465 Swedish RSK No.: 5853378 Country of origin: MX Custom tariff no.: 84137029</p>