

Qty. Description

1 **SQE 5-50**



Note! Product picture may differ from actual product

Product No.: On request

3" multi-stage, submersible pump designed for domestic water supply, liquid transfer in tanks, irrigation and environmental applications. The pump has "floating" impellers, each with its own tungsten carbide/ceramic bearing.

The pump features soft starting and protection against dry-running, upthrust, overvoltage, undervoltage, overload and overtemperature.

The motor is a single-phase motor of the permanent magnet rotor type ensuring optimum efficiency within a wide load range.

The motor is fitted with a replaceable end cover with socket.

Liquid:

Pumped liquid:	Water
Liquid max temp:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³

Technical:

Pump speed on which pump data are based:	10700 rpm
Rated flow:	5 m ³ /h
Rated head:	48 m
Approvals:	CE,PCBC,RCM,EAC,CN RoHS Exempt,Morocco
Curve tolerance:	ISO9906:2012 3B

Materials:

Pump:	Polyamide / Stainless steel DIN W.-Nr. 1.4301 AISI 304
Impeller:	Polyamide
Motor:	Stainless steel DIN W.-Nr. 1.4301 AISI 304

Installation:

Pump outlet:	Rp1 1/2
Minimum borehole diameter:	76 mm

Electrical data:

Motor type:	MSE3
Power input - P1:	2.05 kW
Rated power - P2:	1.55 kW
Power input P3:	1.22 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 200-240 V
Rated current:	11.2 A



Company name: Tengj ehf




Created by:

Phone:

Date: 03/02/2022

Qty.	Description
	Power factor: 1.00
	Rated speed: 10700 rpm
	Start. method: direct-on-line
	Enclosure class (IEC 34-5): IP68
	Insulation class (IEC 85): F
	Length of cable: 1.5 m
	Motor No: 96160856
	Others:
	Net weight: 6.8 kg
	Gross weight: 6.8 kg
	Shipping volume: 0.01 m ³
	Danish VVS No.: 388445450
	Swedish RSK No.: 5853385
	Norwegian NRF no.: 9041357
	Country of origin: MX
	Custom tariff no.: 84137029

Description	Value
General information:	
Product name:	SQE 5-50
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	10700 rpm
Rated flow:	5 m ³ /h
Rated head:	48 m
Stages:	4
Approvals:	CE,PCBC,RCM,EAC,CN RoHS Exempt,Morocco
Curve tolerance:	ISO9906:2012 3B
Pump No:	96080399
Model:	B
Valve:	pump with built-in non-return valve
Materials:	
Pump:	Polyamide / Stainless steel
Pump:	DIN W.-Nr. 1.4301
Pump:	AISI 304
Impeller:	Polyamide
Motor:	Stainless steel
Motor:	DIN W.-Nr. 1.4301
Motor:	AISI 304
Installation:	
Pump outlet:	Rp1 1/2
Minimum borehole diameter:	76 mm
Liquid:	
Pumped liquid:	Water
Liquid max temp:	35 °C
Max liquid t at 0.15 m/sec:	35 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	MSE3
Power input - P1:	2.05 kW
Rated power - P2:	1.55 kW
Power input P3:	1.22 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 200-240 V
Rated current:	11.2 A
Power factor:	1.00
Rated speed:	10700 rpm
Start. method:	direct-on-line
Enclosure class (IEC 34-5):	IP68
Insulation class (IEC 85):	F
Built-in motor protection:	Y
Thermal protec:	internal
Length of cable:	1.5 m
Motor No:	96160856
Controls:	
CU 300/CU 301:	communication with CU 300/CU 301 possible
Others:	
Net weight:	6.8 kg
Gross weight:	6.8 kg
Shipping volume:	0.01 m ³
Sales region:	EU/S-AMREG/APREG





Company name: Tengi ehf


Created by:

Phone:

Date: 03/02/2022


Description	Value
Danish VVS No.:	388445450
Swedish RSK No.:	5853385
Norwegian NRF no.:	9041357
Country of origin:	MX
Custom tariff no.:	84137029

On request SQE 5-50



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request SQE 5-50



Note! All units are in [mm] unless others are stated.