

Description	Value
-------------	-------

General information:

Product name:	LC 241 2 x 9-23 DOL 3X230/400 PI OPT
Product No:	On request
EAN number:	On request

Technical:

Approvals:	CE, EAC
Number of pumps:	2

Materials:

Cabinet:	Plastic
----------	---------

Installation:

Range of ambient temperature:	-20 .. 45 °C
Cabinet mounting:	Wall mounting
Earth connection:	N, PE

Electrical data:

Mains frequency:	50 / 60 Hz
Rated voltage:	3 x 220-240/380-415 V
Rated current:	9-23 A
Capacitor size - run capacitor:	N/A µF
Capacitor size - starting capacitor:	N/A µF

Method of start:	Direct-on-line (DOL)
Enclosure class (IEC 34-5):	IP54
Back-up fuse required:	50 A

Controls:

Fault light for system (Yes/No):	N
Communication interface module (Yes/No):	N
Hand/Off/Auto switch (Yes/No):	N
Ex barrier analog (Yes/No):	N
Ex barrier digital (Yes/No):	N
Current measurement (Yes/No):	Y
IO 241 (Yes/No):	N
Battery back-up (Yes/No):	N
Mains switch (Yes/No):	N
Electrode-relay (Yes/No):	N
RCD panel (Yes/No):	N
RCD per pump (Yes/No):	N
Circuit breaker per pump (Yes/No):	N

Others:

Net weight:	11.5 kg
Gross weight:	12.7 kg
Shipping volume:	0.083 m ³
Country of origin:	DK
Custom tariff no.:	85371098

