


Qty.	Description
1	<p data-bbox="199 327 486 360">Unilift AP35B.50.06.A1.V</p> <div data-bbox="300 383 470 696" style="text-align: center;">  </div> <p data-bbox="592 680 1062 707" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="199 714 491 770">Product No.: 96468356 Submersible effluent pump</p> <p data-bbox="199 801 718 891">Vertical single-stage stainless steel submersible pump with integrated submersible 1-phase motor.</p> <p data-bbox="199 922 699 1039">The pump is fitted with ring stand and carrying handle and is supplied with a 10 m mains cable and a level switch for automatic start and stop.</p> <p data-bbox="199 1070 679 1187">The impeller is a V impeller for 35 mm free passage suitable for pumping surface water, groundwater, wastewater and similar.</p> <p data-bbox="199 1218 722 1308">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="199 1339 735 1429">The motor is insulation class F with thermal overload protection and has long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="199 1460 663 1550">The pump has R 2" discharge port and is ready for installation either free-standing or on an auto-coupling system.</p> <p data-bbox="199 1581 793 1697">Liquid: Pumped liquid: Any Newtonian liquid Liquid max temp: 40 °C Density: 998.2 kg/m³</p> <p data-bbox="199 1729 1007 1845">Technical: Type of impeller: V Maximum particle size: 35 mm Approvals: CE,VDE,EAC,RCM,LGABG,TUVRHWID,</p> <p data-bbox="199 1877 766 1989">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p data-bbox="199 1998 766 2087">Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p>

Qty.	Description
	<p>Installation:</p> <p>Range of ambient temperature: 0 .. 40 °C</p> <p>Pump outlet: R 2"</p> <p>Maximum installation depth: 7 m</p> <p>Auto-coupling: Y</p> <p>Electrical data:</p> <p>Motor type 1-phase: PSC</p> <p>Power input - P1: 1 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 230 V</p> <p>Rated current: 4.6 A</p> <p>Cos phi - power factor: 0.98</p> <p>Rated speed: 2810 rpm</p> <p>Capacitor size - run: 16 µF/400 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 10 m</p> <p>Type of cable plug: SCHUKO</p> <p>Others:</p> <p>Net weight: 10.5 kg</p> <p>Gross weight: 12.2 kg</p> <p>Danish VVS No.: 391270322</p> <p>Swedish RSK No.: 5886038</p> <p>Country of origin: HU</p> <p>Custom tariff no.: 84137021</p>