


Qty.	Description
1	<p data-bbox="201 338 485 365">UNILIFT AP50.50.08.A1V</p>  <p data-bbox="592 685 1062 707" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="201 719 560 775">Product No.: 96010984 Submersible drainage pump type</p> <p data-bbox="201 804 719 949">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase totally enclosed motor in insulation class F with thermal overload protection.</p> <p data-bbox="201 983 663 1039">The pump is fitted with suction strainer and level switch for automatic start and stop.</p> <p data-bbox="201 1072 663 1189">The impeller is a V impeller for 50 mm free passage suitable for pumping groundwater, surface water, rain water and similar.</p> <p data-bbox="201 1223 724 1308">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="201 1341 711 1458">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="201 1491 724 1666">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="201 1700 794 1816">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p data-bbox="201 1850 644 1935">Technical: Type of impeller: V Maximum particle size: 50 mm</p> <p data-bbox="201 1968 767 2085">Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p>

Qty.	Description
	<p>Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304</p> <p>Cable union: Brass CW602N C35330</p> <p>Installation: Range of ambient temperature: 0 .. 55 °C Pump outlet: Rp 2 Maximum installation depth: 7 m</p> <p>Electrical data: Motor type 1-phase: PSC Power input - P1: 1.3 kW Mains frequency: 50 Hz Rated voltage: 1 x 230 V Rated current: 5.9 A Cos phi - power factor: 0.99 Rated speed: 2790 rpm Capacitor size - run: 16 µF/400 V Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: SCHUKO</p> <p>Others: Net weight: 16.3 kg Gross weight: 17.5 kg Danish VVS No.: 391321312 Swedish RSK No.: 5885793 Finnish LVI No.: 4822572 Norwegian NRF no.: 9045685 Country of origin: HU Custom tariff no.: 84137021</p>