

Qty. Description

1 UNILIFT AP50.50.11.3V



Note! Product picture may differ from actual product

Product No.: [96010562](#)

Submersible drainage pump type

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.

The impeller is a V impeller for 50 mm free passage suitable for pumping groundwater, surface water, rain water and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.

The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 55 °C

Density: 998.2 kg/m³

Technical:

Type of impeller: V

Maximum particle size: 50 mm

Materials:

Pump housing: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Impeller: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Qty.	Description
	<p>Cable union: Brass CW602N C35330</p> <p>Installation: Range of ambient temperature: 0 .. 55 °C Pump outlet: Rp 2 Maximum installation depth: 7 m</p> <p>Electrical data: Power input - P1: 1.9 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 3 A Cos phi - power factor: 0.88 Rated speed: 2785 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE</p> <p>Others: Net weight: 14 kg Gross weight: 14.7 kg Danish VVS No.: 391322132 Swedish RSK No.: 5880120 Finnish LVI No.: 4822585 Country of origin: HU Custom tariff no.: 84137021</p>