

Qty. Description

1 **Unilift AP50B.50.11.1.V**



Note! Product picture may differ from actual product

Product No.: [96004599](#)

Submersible effluent pump

Vertical single-stage stainless steel submersible pump with integrated submersible 1-phase motor.

The pump is fitted with ring stand and carrying handle and is supplied with a 10 m mains cable.

The impeller is a V impeller for 50 mm free passage suitable for pumping surface water, groundwater, wastewater and similar.

The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.

The motor is insulation class F with thermal overload protection and has long-life deep-groove greased-for-life ball bearings.

The pump has R 2" discharge port and is ready for installation either free-standing or on an auto-coupling system.

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid max temp: 40 °C

Density: 998.2 kg/m³

Technical:

Type of impeller: V

Maximum particle size: 50 mm

Approvals: CE,VDE,EAC,RCM,LGABG,MORO,UKCA

Materials:

Pump housing: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Impeller: Stainless steel
DIN W.-Nr. 1.4301
AISI 304

Qty.	Description
	<p>Installation:</p> <p>Range of ambient temperature: 0 .. 40 °C</p> <p>Pump outlet: R 2"</p> <p>Maximum installation depth: 7 m</p> <p>Auto-coupling: Y</p> <p>Electrical data:</p> <p>Motor type 1-phase: PSC</p> <p>Power input - P1: 1.75 kW</p> <p>Mains frequency: 50 Hz</p> <p>Rated voltage: 1 x 230 V</p> <p>Rated current: 8 A</p> <p>Cos phi - power factor: 0.95</p> <p>Rated speed: 2760 rpm</p> <p>Capacitor size - run: 20 µF/400 V</p> <p>Enclosure class (IEC 34-5): IP68</p> <p>Insulation class (IEC 85): F</p> <p>Length of cable: 10 m</p> <p>Type of cable plug: SCHUKO</p> <p>Others:</p> <p>Net weight: 11.5 kg</p> <p>Gross weight: 12.5 kg</p> <p>Danish VVS No.: 391272132</p> <p>Swedish RSK No.: 5885939</p> <p>Finnish LVI No.: 4822591</p> <p>Country of origin: HU</p> <p>Custom tariff no.: 84137021</p>