

Qty. Description

1 UNILIFT KP150-M-1



Note! Product picture may differ from actual product

Product No.: [011H1300](#)

Submersible drainage pump

Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 1-phase canned motor in insulation class F with thermal overload protection.

The pump is fitted with a suction strainer, a carrying handle and is supplied with a 10 m mains cable.

The impeller is a semi-open impeller for 10 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.

The pump has a double shaft seal consisting of two lip seals with grease in-between.

The pump has an outer casing ensuring continuous cooling of the motor by the pumped liquid. The rotor shaft operates in two maintenance-free carbon bearings cooled by the pumped liquid

The motor is filled with a non-toxic motor liquid.

Liquid:

Pumped liquid: Any Newtonian liquid

Liquid temperature range: 0 .. 50 °C

Density: 998.2 kg/m³

Technical:

Maximum flow: 2.36 l/s

Max. Particle: 10 mm

Materials:

Pump housing: Stainless steel
EN 1.4301
AISI 304

Impeller: Stainless steel
EN 1.4301
AISI 304

Installation:

Range of ambient temperature: 0 .. 50 °C



Company name: Tengi ehf

Created by:

Phone:

Date: 11/02/2022

| Qty. | Description |
|------|-------------|
|------|-------------|

| | |
|-----------------------------|------------|
| Type of connection: | Rp |
| Size of connection: | 1 1/4 inch |
| Maximum installation depth: | 7 m |

| | |
|-----------------------------|---------------|
| Electrical data: | |
| Power input - P1: | 300 W |
| Mains frequency: | 50 Hz |
| Rated voltage: | 1 x 220-230 V |
| Rated current: | 1.3 A |
| Capacitor size - run: | 8 µF/400 V |
| Enclosure class (IEC 34-5): | IP68 |
| Insulation class (IEC 85): | F |
| Length of power cable: | 10 m |
| Type of cable plug: | SCHUKO |

| | |
|--------------------|----------------------|
| Others: | |
| Net weight: | 5.93 kg |
| Gross weight: | 6.63 kg |
| Shipping volume: | 0.013 m ³ |
| Danish VVS No.: | 391214015 |
| Swedish RSK No.: | 5885708 |
| Finnish LVI No.: | 4822501 |
| Norwegian NRF no.: | 9040792 |
| Country of origin: | HU |
| Custom tariff no.: | 84137021 |