

Description	Value
<b>General information:</b>	
Product name:	JP 5-48 S-BBVP
Product No:	On request
EAN number:	On request
<b>Technical:</b>	
Rated flow:	5 m <sup>3</sup> /h
Head max:	48.3 m
Head max:	48.3 m
Primary shaft seal:	BBVP
Approvals on nameplate:	CE,EAC
Curve tolerance:	ISO9906:2012 3B
Model:	A
Rated driver speed:	2800 rpm
<b>Materials:</b>	
Pump housing:	Stainless steel
Pump housing:	EN 1.4301
Pump housing:	AISI 304
Impeller:	Composite
Material code:	S
<b>Installation:</b>	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	6 bar
Maximum permissible inlet pressure:	1 bar
Pump inlet:	G1
Pump outlet:	G1
<b>Liquid:</b>	
Pumped liquid:	Water
Liquid temperature range:	0 .. 40 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m <sup>3</sup>
<b>Electrical data:</b>	
Power input - P1:	1490 W
Rated power - P2:	1.014 kW
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Rated current:	6.6 A
Starting current:	27.9 A
Capacitor size - run:	25 µF/450 V
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	F
Type of cable plug:	SCHUKO
Cable:	Y
<b>Controls:</b>	
Presscontrol:	without press control
Switch:	on/off switch not included
<b>Others:</b>	
Net weight:	12 kg
Gross weight:	14 kg
Shipping volume:	0.026 m <sup>3</sup>
Danish VVS No.:	385534050
Swedish RSK No.:	5928696
Finnish LVI No.:	4732538
Norwegian NRF no.:	9040047
Country of origin:	HU
Custom tariff no.:	84137051

