


Qty.	Description
1	<p data-bbox="199 338 427 365">GT-H-35 PN10 G1 V</p> <div data-bbox="300 392 483 689" style="text-align: center;">  </div> <p data-bbox="592 685 1062 707" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="199 719 478 741">Product No.: On request</p> <p data-bbox="199 779 1452 853">Grundfos GT-H-35 PN10 G1 V is a diaphragm pressure tank, with a capacity of 35.0 l and Vertical installation. The tanks are approved for drinking water. The GT-H-35 PN10 G1 V is designed for a maximum operation pressure of 10 bar and a maximum liquid temperature of 90 °C.</p> <p data-bbox="199 954 1414 1003">The tank is a steel pressure tank with a non-toxic butyl rubber diaphragm with a precision-moulded polypropylene liner for superior air and water separation.</p> <p data-bbox="199 1070 1457 1120">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="199 1128 1442 1202">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="199 1274 1457 1323">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="199 1332 1442 1406">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="199 1451 1292 1565">The tanks have a non-replaceable diaphragm that is pre-charged with nitrogen (1.5 bar). The tanks have a non-toxic butyl rubber diaphragm, dividing the tank chamber into two compartments. The upper compartment contains compressed nitrogen. The lower compartment has a liner of polypropylene (PP) and is filled with water from the pump.</p> <p data-bbox="199 1599 1437 1731">A pressure tank ensures controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss. The result is increased comfort in your installation by limiting the start/stop frequency of your pump, and it increases system comfort by compensating for pressure drops when a tap is opened, while reducing problems with water hammer in the pipework.</p> <p data-bbox="199 1803 628 1856">Liquid: Liquid max temp: 90 °C</p> <p data-bbox="199 1890 681 1944">Technical: Membrane type: diaphragm</p> <p data-bbox="199 1977 877 2031">Materials: Basic: Carbon steel / Polypropylene</p> <p data-bbox="199 2065 325 2087">Installation:</p>



Company name: Tengi ehf

Created by:

Phone:

Date: 11/02/2022

Qty.	Description
	<p>Maximum operating pressure: 10 bar Type of connection: G Size of connection: 1 inch Size: 35.0</p> <p>Others:</p> <p>Net weight: 6.6 kg Gross weight: 7.4 kg Applicat. typ: Standard Danish VVS No.: 398254733 Norwegian NRF no.: 8402812 Country of origin: TW Custom tariff no.: 84798997</p>

Description	Value
General information:	
Product name:	GT-H-35 PN10 G1 V
Product No:	On request
EAN number:	On request
Technical:	
Membrane type:	diaphragm
Materials:	
Basic:	Carbon steel / Polypropylene
Installation:	
Maximum operating pressure:	10 bar
Pre-pressure:	1.9 bar
Type of connection:	G
Size of connection:	1 inch
Installation:	Vertical
Size:	35.0
Liquid:	
Liquid max temp:	90 °C
Others:	
Net weight:	6.6 kg
Gross weight:	7.4 kg
Applicat. typ:	Standard
Danish VVS No.:	398254733
Norwegian NRF no.:	8402812
Country of origin:	TW
Custom tariff no.:	84798997

