


Qty.	Description
1	<p data-bbox="204 338 443 365">GT-H-8 PN10 G 3/4 V</p> <div data-bbox="300 405 485 685" style="text-align: center;">  </div> <p data-bbox="595 685 1062 707" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="204 719 464 741">Product No.: 96528335</p> <p data-bbox="204 779 1433 853">Grundfos GT-H-8 PN10 G 3/4 V is a diaphragm pressure tank, with a capacity of 8.0 l and Vertical installation. The tanks are approved for drinking water. The GT-H-8 PN10 G 3/4 V is designed for a maximum operation pressure of 10 bar and a maximum liquid temperature of 90 °C.</p> <p data-bbox="204 954 1414 1003">The tank is a steel pressure tank with a non-toxic butyl rubber diaphragm with a precision-moulded polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1070 1455 1120">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1128 1442 1202">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="204 1274 1455 1323">The diaphragm is a chlorine-resistant 100 % butyl diaphragm with a precision-moulded copolymer polypropylene liner for superior air and water separation.</p> <p data-bbox="204 1332 1442 1406">The tank has a FlowThru connection, which constantly flushes the tank while the pump is running. This ensures that the water in the tank remains fresh and eliminates the risk of stagnant water during normal system operation.</p> <p data-bbox="204 1451 1294 1565">The tanks have a non-replaceable diaphragm that is pre-charged with nitrogen (1.5 bar). The tanks have a non-toxic butyl rubber diaphragm, dividing the tank chamber into two compartments. The upper compartment contains compressed nitrogen. The lower compartment has a liner of polypropylene (PP) and is filled with water from the pump.</p> <p data-bbox="204 1599 1437 1731">A pressure tank ensures controlled pressure in the water supply and thereby limits the switching frequency of the pump in case of low water consumption or leakage loss. The result is increased comfort in your installation by limiting the start/stop frequency of your pump, and it increases system comfort by compensating for pressure drops when a tap is opened, while reducing problems with water hammer in the pipework.</p> <p data-bbox="204 1805 628 1856">Liquid: Liquid max temp: 90 °C</p> <p data-bbox="204 1890 683 1942">Technical: Membrane type: diaphragm</p> <p data-bbox="204 1980 879 2031">Materials: Basic: Carbon steel / Polypropylene</p> <p data-bbox="204 2069 325 2092">Installation:</p>



Company name: Tengi ehf

Created by:

Phone:

Date: 11/02/2022

Qty.	Description
	<p>Maximum operating pressure: 10 bar Type of connection: G Size of connection: 3/4 inch Size: 8.0</p> <p>Others:</p> <p>Net weight: 2.1 kg Gross weight: 2.6 kg Applicat. typ: Standard Danish VVS No.: 398254708 Swedish RSK No.: 5950115 Norwegian NRF no.: 8402805 Country of origin: TW Custom tariff no.: 84798997</p>